

Forum:[Hack Forums](#)

Thread: [Skype Resolver Script \[API\]](#)

Flacko. - February 8, 2015, 6:16 pm

This script is for users that already have an API, but may want to resell it for whatever reason(s). I added 2 methods, Skype IP Resolver, and IP2Skype. All you have to do is change the API Keys out with yours.

1. Upload the script to your server, or domain.
2. Format: `api.php?key=1337&method=1&username=echo123`

I added arrays thanks to Yani.

Code <?php

```
$key = $_GET['apiKey'];
$username = $_GET['username'];
$ip = $_GET['ip'];
$method = $_GET['method'];
$blacklist = array(
    'yani',
    'tosca'
);
$key = array(
    '1337'
);
$api1 = "https://example.com/api1.php?key=xxxx&username="; //Skype Resolver API Key 1
$api2 = "https://example.com/api2.php?key=xxxx&username="; //Skype Resolver API Key 2
$api3 = "https://example.com/ip2skype.php?key=xxxx&ip=";

if ($key == null) {
    echo "Please enter your key.";
}
if (in_array($key, $apiKey)) {

    if ($method == null) {
        echo 'Methods Available:</br>';
        echo 'Skype Resolve: ?key=' . $key . '&method=1&username=echo123 </br> IP2Skype: ?key='
        . $key . '&method=2&ip=127.0.0.1';
    }

    if ($method >= 3) {
        echo '[SYNTAX ERROR] Methods Available:</br>';
        echo 'Skype Resolve: ?key=' . $key . '&method=1&username=echo123 </br> IP2Skype: ?key='
        . $key . '&method=2&ip=127.0.0.1';
    }

    if ($method == "1") //METHOD 1 [Skype IP Resolver]
    {
        if ($username == null) {
            echo 'Please enter a username.</br>Syntax: ?key=' . $key . '&method=1&username=echo123';
        } else {
```

```

if (in_array($username, $blacklist)) {
    echo 'Username is blacklisted.';
} else {
    $skype_username_resolve_api1 = file_get_contents(" . $api1 . " . $username . ");
    $skype_username_resolve_api2 = file_get_contents(" . $api2 . " . $username . "); {
    echo 'API1: ' . $skype_username_resolve_api1 . '</br>';
    echo 'API2: ' . $skype_username_resolve_api2 . '</br>';
    echo "<img src='\"http://api.skype.com/users/{\$username}/profile/avatar\"' border=0>";
    }
}
}
}

if ($method == "2") //METHOD 2 [IP2Skype]
{
    if ($ip == null) {
        echo 'Enter an IP Address</br>Syntax: ?key=' . $key . '&method=2&ip=127.0.0.1';
    } else {
        if ($ip == "127.0.0.1" || $ip == "127.0.0.2") { //Replace 127.0.0.1 and 127.0.0.2 with the IP(s) you
dont want to get resolved.
            echo 'IP Address is blacklisted.';
        } else {
            $skype_ip2skype_api1 = file_get_contents(" . $api3 . " . $ip . ");
            echo 'Result: ' . $skype_ip2skype_api . ";
        }
    }
}
} else {
    echo 'Invalid Key.';
}
?>

Old Version:
Spoiler \(Click to View\)
Code <?php
$key    = $_GET['key'];
$username = $_GET['username'];
$ip     = $_GET['ip'];
$method = $_GET['method'];
$login  = "1337"; //Change this to your desired login key.

if ($key == null) {
    echo "Please enter your key.";
}
if ($key == $login) {

    if ($method == null) {
        echo 'Methods Availiable:</br>';
        echo 'Skype Resolve: ?key=' . $key . '&method=1&username=echo123 </br> IP2Skype: ?key='
. $key . '&method=2&ip=127.0.0.1';
    }

    if ($method >= 3) { //Change this to how many methods you have, +1.
        echo '[SYNTAX ERROR] Methods Availiable:</br>';
    }
}

```

```

    echo 'Skype Resolve: ?key=' . $key . '&method=1&username=echo123 </br> IP2Skype: ?key='
    . $key . '&method=2&ip=127.0.0.1';
}

if ($method == "1") //METHOD 1 [Skype IP Resolver]
{
    if ($username == null) {
        echo 'Please enter a username.</br>Syntax: ?key=' . $key . '&method=1&username=echo123';
    } else {
        if ($username == "username1" || $username == "username2") { //Put the usernames you don't
want to be resolved where it says username1, and username2.
            echo 'Username is blacklisted.';
        } else {
            $skype_username_resolve_api1 =
file_get_contents('http://example.com/api.php?key=xxx&username=' . $username . "");
            $skype_username_resolve_api2 =
file_get_contents('http://example.com/api2.php?key=xxx&username=' . $username . ""); {
            echo 'API1: ' . $skype_username_resolve_api1 . '</br>';
            echo 'API2: ' . $skype_username_resolve_api2 . '</br>';
            echo "<img src=\"http://api.skype.com/users/{\$username}/profile/avatar\" border=0>";
        }
    }
}

if ($method == "2") //METHOD 2 [IP2Skype]
{
    if ($ip == null) {
        echo 'Enter an IP Address</br>Syntax: ?key=' . $key . '&method=2&ip=127.0.0.1';
    } else {
        if ($ip == "127.0.0.1" || $ip == "127.0.0.2") { //Replace 127.0.0.1 and 127.0.0.2 with the IP(s) you
dont want to get resolved.
            echo 'IP Address is blacklisted.';
        } else {
            $skype_ip2skype_api1 =
file_get_contents('http://example.com/ip2skype.php?key=xxxx&ip='.$ip.");
            echo 'Result: ' . $skype_ip2skype_api1 . ";
        }
    }
}
} else {
    echo 'Invalid Key.';
}
//Coded by Tosca on HF.
//https://hackforums.net/member.php?action=profile&uid=2236072
?>

```

Sakuto - February 9, 2015, 5:35 am

Better use quick syntax for array creation

```
$blacklist = ['yani', 'tosca'];
```