

Forum:[Hack Forums](#)

Thread: [Setup for \[censored\] using OpenVPN on Linux OS](#)

Proof - November 20, 2020, 1:07 pm

INSTALLATION:

Download the bash script file, and set permissions

```
Code git clone https://github.com/ozankiratli/NordVPNNonOVPN.gitCode sudo cp
/path/NordVPNSetup.sh /usr/local/binCode sudo chmod +x /usr/local/bin
RUNNING:
```

```
Code NordVPNSetup.sh -s <servername> [options [arguments] ]
```

Options:

```
Code -h, --help Display help (this message)
```

- s <ServerName> [censored] server
- p <PortType> Port type TCP or UDP
- N /path/to/NordVPNfiles Defines path to downloaded openvpn files
- C /path/to/openvpn Path to OpenVPN configuration files in the system
- n <VPNServiceName> Name of the configuration filename without .ovpn or .conf
- firstuse Use this flag if you are setting up [censored] client for the first time
- l Lists all available servers
- l --country <CountryCode> Lists servers of the chosen country. Use 2 letter country codes
- l --port <PortType> Lists servers of the chosen port type. TCP or UDP
- l --country <CC> --port <PT> Lists servers of the chosen country and port.
- checkserver <servername> Shows if the server is available and available port types.
- u, --usage Correct usage options
- updatefiles Updates the files
- start <VPNServiceName> Starts service
- stop <VPNServiceName> Stops service
- restart Restarts service
- status <VPNServiceName> Returns service status
- enable <VPNServiceName> Enables service
- disable <VPNServiceName> Disables service

Be aware that -h, -l, --checkserver, -u, --updatefiles, --start, --stop, --restart, -status, --enable, and --disable options will override other options, the first of these options will be processed, the others will be ignored.

Default options are:

```
Code NordVPNSetup.sh -s <ServerName> [default=none] -p <PortType> [default=udp] -C
<path/to/[censored]> [default=/home/romulan/build/[censored]] -O <path/to/OpenVPN>
[default=/etc/openvpn] -f <filename> [default=]
```

USAGE SUGGESTIONS:

Setting [censored]:

```
Code NordVPNSetup.sh -s <ServerName> [default=none] -p <PortType> [default=udp] -C
<path/to/[censored]> [default=/home/romulan/build/[censored]] -O <path/to/OpenVPN>
[default=/etc/openvpn] -f <filename> [default=]
```

For Help:

Code NordVPNSetup.sh -h or NordVPNSetup.sh --help
For Usage: (Displaying this list)

Code NordVPNSetup.sh -u or NordVPNSetup.sh --usage
For Listing Servers:

Code NordVPNSetup.sh -l [--country <2LetterCountryCode>] [--port <PortType>]
For Checking if a Server file is present in the local machine:

Code NordVPNSetup.sh --checkserver <ServerName>
For Updating Server files in the local machine:

Code NordVPNSetup.sh --updatefiles
For Client Services:

Code NordVPNSetup.sh --enable/--disable/--start/--stop/--restart/--status <VPNServiceName>

2xTheTap115 - November 20, 2020, 2:25 pm

A useful tutorial, short and to the point good job OP?

xZalurex - November 20, 2020, 7:28 pm

(Nov 20, 2020 02:07 PM)Proof Wrote: [\[CITE\]](#) INSTALLATION:

Download the bash script file, and set permissions

Code git clone https://github.com/ozankiratli/NordVPNNonOVPN.gitCode sudo cp
/path/NordVPNSetup.sh /usr/local/binCode sudo chmod +x /usr/local/bin
RUNNING:

Code NordVPNSetup.sh -s <servername> [options [arguments]]

Options:

Code -h, --help Display help (this message)

- s <ServerName> [censored] server
- p <PortType> Port type TCP or UDP
- N /path/to/NordVPNfiles Defines path to downloaded openvpn files
- C /path/to/openvpn Path to OpenVPN configuration files in the system
- n <VPNServiceName> Name of the configuration filename without .ovpn or .conf
- firstuse Use this flag if you are setting up [censored] client for the first time
- l Lists all available servers
- l --country <CountryCode> Lists servers of the chosen country. Use 2 letter country codes
- l --port <PortType> Lists servers of the chosen port type. TCP or UDP
- l --country <CC> --port <PT> Lists servers of the chosen country and port.
- checkserver <servername> Shows if the server is available and available port types.
- u, --usage Correct usage options
- updatefiles Updates the files
- start <VPNServiceName> Starts service
- stop <VPNServiceName> Stops service
- restart Restarts service
- status <VPNServiceName> Returns service status
- enable <VPNServiceName> Enables service
- disable <VPNServiceName> Disables service

Be aware that -h, -l, --checkserver, -u, --updatefiles, --start, --stop, --restart, -status, --enable, and

--disable options will override other options, the first of these options will be processed, the others will be ignored.

Default options are:

```
Code NordVPNSetup.sh -s <ServerName> [default=none] -p <PortType> [default=udp] -C  
<path/to/[censored]> [default=/home/romulan/build/[censored]] -O <path/to/OpenVPN>  
[default=/etc/openvpn] -f <filename> [default=]
```

USAGE SUGGESTIONS:

Setting [censored]:

```
Code NordVPNSetup.sh -s <ServerName> [default=none] -p <PortType> [default=udp] -C  
<path/to/[censored]> [default=/home/romulan/build/[censored]] -O <path/to/OpenVPN>  
[default=/etc/openvpn] -f <filename> [default=]
```

For Help:

Code NordVPNSetup.sh -h or NordVPNSetup.sh --help

For Usage: (Displaying this list)

Code NordVPNSetup.sh -u or NordVPNSetup.sh --usage

For Listing Servers:

Code NordVPNSetup.sh -l [--country <2LetterCountryCode>] [--port <PortType>]

For Checking if a Server file is present in the local machine:

Code NordVPNSetup.sh --checkserver <ServerName>

For Updating Server files in the local machine:

Code NordVPNSetup.sh --updatefiles

For Client Services:

Code NordVPNSetup.sh --enable/--disable/--start/--stop/--restart/--status <VPNServiceName>

good work.